## **Technical Data** Metal Switches

## Series GC

Description GC-SU1Z HIW



Article number 6021370629

27

32.5

Ø4; 5.5 deep

Blind hole for fitting pin

62


22

M20x1.5


Operating symbol

$$\begin{array}{c} & \uparrow \\ 13 \xrightarrow{-} 14 \\ (-) 21 \xrightarrow{+} 22 \end{array}$$

### Operating diagram



ON



Electrical data		
Rated insulation voltage	Ui	400 VAC
Conv. thermal current	I <sub>the</sub>	10A
Rated operational voltage	U <sub>e</sub>	240V
Utilization category		AC-15, U <sub>e</sub> /I <sub>e</sub> 240V/3A
Direct opening action	$\ominus$	acc. to IEC/EN 60947-5-1, Annex K
Short-circuit protective device		Fuse 2A gL/gG
Protection class		Ι

5.5

ŝ

62.

This document will not become the contractual basis; the details included herein do not constitute any descriptions of expected conditions, so that warranties/claims for defects on account of possible variations of the actual qualities from the qualities described herein are explicitly excluded. All rights reserved. Specifications subject to change without notice!

Date of issue: 12.02.2007 / Page 1 of 2 Document: 6021370629\_en.doc / Last update: 1 / 2076-07

# Technical Data Metal Switches



### Mechanical data

Die-cast aluminium
Sheet aluminium
Lever (sheet), roller (thermoplastic)
-30°C +80°C
1 NC, 1 NO (Zb)
10 <sup>7</sup> operating cycles
≤ 100 / min.
2 x M4
4 screw terminals (M3,5)
Solid: 0,5 1,5mm <sup>2</sup>
Litz wire with ferrules: 0,5 1,5mm <sup>2</sup>
M20x1,5
≈ 0,16 kg
Operator definable
IP65 acc. to IEC/EN 60529

#### Actuation

By loosening the 4 screws the actuation assembly can be rotated in 90 degree increments such that 4 actuation directions are possible. The actuation assembly is to be again fastened to the housing using the 4 screws.

Standards

VDE 0660 T100, DIN EN 60947-1, IEC 60947-1 VDE 0660 T200, DIN EN 60947-5-1, IEC 60947-5-1

EU Conformity

CE

Approvals

<sub>c</sub>CSA<sub>US</sub> A300 (same polarity)

### Notes

The degree of protection specified (IP code) applies only to a properly closed cover and the use of an equivalent cable gland with adequate cable.

This document will not become the contractual basis; the details included herein do not constitute any descriptions of expected conditions, so that warranties/claims for defects on account of possible variations of the actual qualities from the qualities described herein are explicitly excluded. All rights reserved. Specifications subject to change without notice!

Date of issue: 12.02.2007 / Page 2 of 2 Document: 6021370629\_en.doc / Last update: 1 / 2076-07