

PROFESSIONAL

Trade & professional / Sensors / Presence Detectors / IR Quattro

IR Quattro

Information copy

Squaring the circle. Infrared presence detector Presence Control PRO IR Quattro KNX for indoors, ideal for small offices, store, service and utility rooms, washrooms and WCs, installation height up to 8 m, with digital BUS interface for controlling 4 lighting channels and HVAC, 1760 switching zones for excellent detection quality, square presence detection zone covering 16 m2, mechanically scalable.





Details

Live life conveniently and save energy too.

More quality of life, more safety and security and more energy saved with intelligent sensor technology from STEINEL.

Light ON / OFF - automatically.

Highly innovative sensors respond to movements and light levels, automatically and instantaneously switching the light ON and OFF again after a preselected time.

The Presence Control PRO IR Quattro KNX infrared presence detector with the unique square detection zone and KNX interface. For detecting presence, controlling lighting with light-level controller and a HVAC controller for the KNX bus. The sensor system with 1760 switching zones guarantees excellent detection quality: 4 x 4 m presence detection, 5 x 5 m radial detection and 7 x 7 m tangential detection. Rectangular-zone detection and the mechanical capability of infinitely scaling reach provide the last word in planning precision. Additional functions provided by ETS software, remote control and bus for as many as 4 light channels permit adjustment to the

particular usage situation (IQ mode for automatically adjusting stay-ON time to room usage, basic brightness, constant-lighting control, automatic room surveillance for switching on HVAC when a room is actually being used etc.). The detection zone can be extended by interconnecting master/master or master/slave detectors. Optionally available remote controls take the effort out of installing and using this system.

14,8w





14,8 W 1184 lm

5 years functional warranty

ideal 2,5 - 8 m

IQ-mode

indoor sensor









infrared sensor

KNX 4 channel max. 4m x 4m presence energy saving





Optional remote controls

Optional surface-mounting adapters (IP 54, KNX)





Optional guard cage

Impulser Wireless



Presence Control PRO IR Quattro HD installation height 2.8 m (white = tangential orange = radial grey = presence)

Technical specifications IR Quattro KNX

STEINEL Professional IR Quattro KNX |

European Article Number (EAN)	4007841008772
Dimensions	120 x 120 x 76 mm
Model	Presence detector
Power supply	KNX bus voltage
Sensor type	Passive infrared
Installation	Ceiling
Recommended installation height	2.50-8.00 m
Sensor system	13 detection levels br/> 1760 switching zones
Application	inside buildings
Square presence detection zone	4 x 4 m max. (16m²)
Square radial detection zone	5 x 5 m max. (25m²)
Square tangential detection zone	7 x 7 m max. (49m²)
Reach mechanically adjustable	Yes
Settings	by means of ETS software, remote control or bus
Lighting channels Light 1 - Light 4	Switching/dimming, switching mode, constant lighting control, stay-ON time
Basic brightness	Permanently ON, 1 – 255 min, 10-50% = all night
Switch-'ON' delay	Room surveillance, 0-255 min., Stay-ON time 1-255 min.
Presence stay "ON" time output	1-255 sec. or 1-255 min.
HVAC output	depending on presence
Further outputs	Light level, sabotage protection
Light level output	in lux
IP rating	IP20

IP rating with AP Box (surface-mounting box)	IP54
Protection class	II
Temperature range	-25-+55
Model	KNX

Application

indoors

up to a mounting height of 8m

small offices, storerooms, service rooms and utility rooms, washrooms and WCs