

OFFER NO. :	15/01/2016	DATE OF DOC. :	15/01/16
	81/2016 POS. 1		
PRODUCT CODE :	P41506100100410		
D.C. MOTOR TYPE:	P 180 M 4 - 06 PVA/1001		
QUANTITY :	1	DELIVERY TIME:	0
BUYER :	IMPEXRON GMBH		



SC/MR

ELECTRICAL DATA

POWER (KW) :78,00/
 ARM. VOLT. (V) :500,00/
 SPEED (RPM) :1610/
 ARM. CURR. (A) :175,00/
 FIELD CURR(A) : 4,28/
 NO. OF POLES : 4

DUTY : S1
 SUPPLY : T.F.C.B.
 ECCITAZ. : SEPARATE WITHOUT STAB.SERIES

INS. CLASS : H DT H
 FIELD VOLT(V): 340,00/170,00

MECHANICAL DATA

ENVIRONMENT : NORMAL ENVIRONMENT
 MOUNTING (IM) : 1001 B3
 PROTECTION (IP) : 23 S
 FAN SUPPLY : 230/400V +/- 10% 50HZ THREEPHASE
 DIRECT COUPLING
 VIBRATION GRADE : N
 SHAFT MATERIAL : STANDARD
 D.E. SHAFT : SPECIAL DIAM. (MM) : 60 m6
 D.E BEARING : BALL

ALTITUDE (MT.) : 1000

COOLING (IC) : 06 PVA

TERMINAL BOX : STANDARD - TOP

LENGTH (MM) : 140 WITH KEY

PAINTING : STANDARD - CYCLE N. 1
 RAL : 6011

INCORPORATED ACCESSORIES

THERMAL PROTECTION: 1-KLIXON ON AUXILIARY POLE
 FILTER

ACCESS. PROVISIONS

PROVISION FOR TACHO/ENCODER: HOLLOW SHAFT
 TACHOG./ENCODER : RDC215 MF 60V-1000rpm IP55

- PROVISION ONLY -

GENERAL DATA

REFERENCE TEMP. : 40 C.

CUSTOMER SPECIFICATION :

ELECTRIC STANDARDS. : CEI,IEC
 NAMEPLATE : ITALIAN
 SCHEMA : R.E.00.20.0352.
 NDE BEARING : 6310-2Z/C3
 MOMENT OF INERTIA J (KGM2) :0,5600

D.E. BEARING : 6313-2Z/C3
 TOTAL WEIGHT (KG) : 420,00
 DYNAMIC LOAD OF SHORT CIRCUIT (KG) :1691
 AC COOLING FAN MOTOR :90 - 2P 2,2 KW - 9,52/5,50 A
 PACKING : ON PALLET