

ERMETO DIN MALE STUD HIGH PRESSURE HYDRAULIC TUBE FITTINGS

✉ Email 🖨 Print



EO-2 fittings have elastomeric seals on all joints for reliable, leak free operation without retightening. EO-2 is designed for metric tube, according German standards DIN 3861 and DIN 2353, now represented by international standard ISO 8434-1.

PART NUMBER:

GE25ZSR3/4EDCF

SERIES:

Heavy

CONNECTION 1 STYLE:

Male BSPP thread - ED (ISO 1179)

CONNECTION 2 STYLE:

24° cone end

CONNECTION 2 TUBE O.D. (MM):

25

CONNECTION SIZE:

G 3/4 A

SHAPE:

Straight male stud connector

FITTING MATERIAL:

Steel, Chromium-6 Free

PRE-INSTALLED OPTIONAL ACCESSORIES:

Pre-assembled with EO-2 functional nut

[Reset Attributes](#)**WHERE TO BUY****PRODUCT OVERVIEW****TECH SPECIFICATIONS**

Print Tech Specifications

PERFORMANCE CHARACTERISTICS**CONNECTION SIZE**

G 1/8 A to G 1 1/2 A; M 10x1.0 to M48x2.0; 7/16-20UNF-2A to 1 5/8-12UN-2A; 1/8-27 NPT to 1 1/2-11.5 NPT

CONNECTION 2 TUBE O.D. (MM)

04 to 42

CONNECTION 2 STYLE

EO 24° cone end

SERIES

Very light, Light, Heavy

CONNECTION 1 STYLE

Male metric thread - O-ring (ISO 6149), Male metric thread - ED (ISO 9974), Male BSPP thread - ED (ISO 1179), Male BSPP thread - metal sealing edge (ISO 1179), Male short BSPT taper thread (DIN 3852-2, type C), Male metric thread - metal sealing edge (ISO 9974), Male short metric taper thread (DIN 3852-1, type C), Male UNF/UN thread - O-ring (ISO 11926), Male NPT thread (SAE J476)

FITTING MATERIAL

Steel Cr(VI)-free, Stainless steel

SHAPE

Straight male stud connector

PRE-INSTALLED OPTIONAL ACCESSORIES

Ermeto DIN male stud high pressure hydraulic tube fittings_Desc_Pre-installed Optional Accessories

[Print Tech Specifications](#)

PRODUCT SUPPORT

RECOMMENDED



Assembly O/EO-2 fittings



Cutting and bending tools



Seamless EO tubes and tube bends



Accessories for Ermeto hydraulic DIN fittings

CONTACT US

Parker Hannifin Manufacturing Germany GmbH & Co. KG

Tube Fittings Division Europe
Am Metallwerk 9
33659 Bielefeld, Germany

Phone
+49 (0) 521-4048-0

Fax
+49 (0) 521-4048-4280

Parker Hannifin

[Products](#)

[About Parker](#)

[Investors](#)

[Community](#)

[Careers](#)

Global Operations