


Panel Mount GFCI

with "Hi/Lo" Voltage Detection



Leviton's new Panel Mount Ground Fault Circuit Interrupter (GFCI) provides personnel protection for equipment that requires a panel mount or bulkhead mount device. The GFCI is designed for convenient mounting and built for heavy duty applications. It is perfect for a variety of applications, including portable power distribution equipment, industrial panels, marine power pedestals and boat lifts.

Features and Benefits:


- Provides UL 943 Class A GFCI protection (5mA±1mA)
- A "Hi/Lo" voltage detection RED indicator lights when power supply swells or drops at approximately 160V RMS / 70V RMS (+/-10%)
- Rated 20A-120 VAC for down-stream loads; units can be easily added to equipment panels as needed
- Rugged, UV/impact-resistant polycarbonate high-visibility yellow housing, with moisture-resistant TEST and RESET buttons
- Rainproof outdoor rated GFCI module
- Automatically resets ON after power interruption
- Open-neutral protection ensures that the GFCI will trip automatically if there's a break in the neutral conductor feeding power to the GFCI
- Meets OSHA requirements for construction sites
- Backed by Leviton's Two-Year Limited Warranty




Specifications

•		
Environmental Specifications		
Flammability	Rated V-2 per UL 94	
Operating Temperature	-35C to 66C	
Mechanical Specifications		
Wire Leads	#12 AWG stranded; Black (Hot), White (Neutral), 15" L	
Wire Type	AWM-TEW (105°C, 600V)	
Product ID	Ratings Permanently Marked on Device	
Standards and Certifications		
ANSI	C-73	
UL 943	Class A (GFCI) with Open Neutral Protection	
UL Recognized Component	E-48380	
CSA C22.2	File LR-57811	
NOM	057	
Warranty	2 Year Limited	
Electrical Specifications		
Amperage	20A	
Voltage	120 VAC	
Frequency	60Hz	
Short Circuit Current Rating (SCCR)	2 kA	
Hi/Lo Voltage Detection	High Voltage Detection 160V RMS +/- 10%	
	Low Voltage Detection 70V RMS +/- 10%	
Material Specifications		
Front Cover	UV-Rated, Impact Resistant Polycarbonate	
Back Cover	UV-Rated, Impact Resistant Polycarbonate	
Performance Data		
Diagnostics	Indicator Lights for Hi/Lo Voltage Detection and Load-Side Power Status	

Dimensional Drawings





Ordering Information

Cat. No.	Description
46596-Y	Panel Mount GFCI, Rated 20A-120VAC, Yellow Housing

^{*} Black Housing available by special request; minimum order quantities apply

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

Telephone: 1-800-323-8920 • Fax: 1-800-832-9538 • Tech Line (8:30AM-7:00PM E.S.T. Monday-Friday): 1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Blvd, Pointe-Claire, QC H9R 1E9 Telephone: 1-800-469-7890 • Fax: 1-800-563-1853

Leviton S. de R.L. de C.V.

Lago Tana 43, Col. Huichapan, Miguel Hidalgo, CP 11290 México DF Telephone: (+52) 55-5082-1040 • Fax: (+52) 55-5386-1797 • www.leviton.com.mx



