productinformation

tesa® 51025 PV10

Handtearable PET cloth tape for basic bundling

tesa® 51025 PV10 is a PET cloth wire harness tape with a solvent-free rubber based adhesive.

Major Features:

- Temperature resistance 125°C/3000h
- Solvent-free adhesive
- Handtearable

Color: Black

Main Application

tesa® 51025 PV10 is designed for the passenger compartment for basic bundling up to a temperature of 125°C.

Technical Data

Backing material Total thickness Type of adhesive Adhesion to steel Elongation at break Tensile strength Temperature resistance min.	PET cloth 160 μm rubber based 6.5 N/cm 25 % 80 N/cm -40 °C		Temperature resistance (3000h) Abrasion resistance (10mm mandrel) Abrasion resistance (5mm mandrel) Flame resistance as composite Unwind force (roll width ≤ 9mm) Unwind force (roll width > 9mm) Noise damping (decibel)	125 °C Class B (acc. to LV312) Class A (acc. to LV312) Class B (acc. to LV312) 8 N/roll (30 m/min) 8 N/roll (30 m/min) Class A (acc. to
		•	Noise damping (decibel)	Class A (acc. to LV312)

Additional Information

Standard widths: 9, 19, 25, 32, 38 mm Standard lengths: 25, 50 m

- Most combinations of width and length are possible
- Further dimensions are available upon request
- Standard core diameter: 38 mm

glad to support you.

For latest information on this product please visit http://l.tesa.com/?ip=51025